



Weldment TLT Axial Fan Impeller Parts Impeller Hub 1412*380mm

Our Product Introduction

Basic Information

- Place of Origin: Shanghai
- Brand Name: YIKU
- Model Number: S1GA4493
- Minimum Order Quantity: 1 piece
- Price: negotiable
- Packaging Details: Wooden box
- Delivery Time: 2-3month
- Supply Ability: 10 units/month



Product Specification

- Hub Diameter: 1412mm
- Hub Aperture: 175mm
- Maximum Speed: 1490r/min
- Grease: 7014
- Model: S1GA4493
- Material: Weldment
- Highlight: TLT Axial Fan Impeller hub,
Impeller hub 1412mm,
Weldment Axial Fan Impeller Parts

for more products please visit us on axialfanparts.com

Product Description

Impeller hub $\phi 1412 \times 380$

1, 按KM007 平衡

(1) 叶 最大工作 速1490r/min

(2) 平衡等 按G1.6 允 的残余不平衡量 面 4750g-mm, 在 个面上配重

(3) 平衡重厚度不大于10mm

2, 量按DIN8563的第三部分BS和BK的等 施工及

3, 后 清除 渣, 并作出 力退火 理

4, 接 量按JB/T10213-2000的 定

5, 托, 盖 与 接 作100%探

6, 加工完成后, 底清理, 不得留有 物

叶 接, 其它 叶 重量比, 性矩也小. 叶片和叶柄等 装件的 心力通 平面推力球 承 至叶 的支承 上. 叶 装件在出厂前已 行多次 平衡.

1, according to KM007 more balanced

(1) Maximum working speed of the impeller 1490r/min

(2) The balance level is 4750g-mm on each side according to the residual unbalance allowed by G1.6, and the weight is balanced on both sides

(3) The thickness of the balance weight is not more than 10mm

2. Weld quality shall be constructed and inspected according to the third part BS and BK of DIN8563

3, welding slag should be removed after welding, and stress annealing treatment

4, welding quality according to JB/T10213-2000 regulations

5, the welding seam of the tray, cover plate and wheel hub should be 100% inspection

6, after the completion of processing, thoroughly clean up, no debris left



Shanghai YIKU Power Equipment Co., Ltd



8613916002258



657925203@qq.com



axialfanparts.com

5587 Dongchuan Road, Pudong New Area, Shanghai